

STOPAQ® CPS

Product Information

Product description: Stopaq® CPS is a penetrating sealing agent used as adhesion promotor in applications of Stopaq® coating systems applied on wet surfaces. When applied on wet steel substrates it will modify the surface character, which enables fast application and enhances adhesion of consecutively applied corrosion preventing Stopaq® products designed for wet application such as Stopaq® Wrappingband SZ, and Stopaq® Paste SZ.

Features:

- Enhances adhesion of Stopaq® corrosion preventing products designed for wet application
- Fully merges with consecutively applied Stopaq® corrosion prevention products designed for wet application

Benefits:

- Cold applied
- Easy to apply, does not require special tools or equipment
- Enables fast application of Stopaq® products designed for wet application

Application examples

Submerged steel structures: As adhesion promotor for Stopaq® underwater corrosion preventing coating systems comprising Stopaq® Wrappingband SZ and consecutively applied Stopaq® materials.

Product properties of Stopaq® CPS

Colour	White, opaque	
Temperature range	Service:	Max. +50°C

Application instruction - Brief version

See specific application instructions available at Seal For Life Industries b.v. for application on wet surfaces

Substrate cleaning	Surfaces should be cleaned according to the specific application instructions prior to application of Stopaq® CPS
CPS application	Take a portion of Stopaq® CPS and put it on the surface to be treated. Spread the material over the entire surface and rub it fiercely onto the substrate e.g. by using a firm sponge or cloth. Remove excess material but make sure that all surface parts still have a thin film of CPS.
Application of consecutively applied materials	Application of consecutively Stopaq® corrosion preventing coating materials should be done within the shortest time possible after application of CPS.

Information

Documentation	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending email to info@stopaq.com
Certified staff	Application of the described coating system should be carried out by certified personnel.

General order information

Product	Stopaq® CPS is available in cartridges <u>Product dimensions and contents:</u> Cartridge 310 ml, 25 pcs/box
Handling	Handle with care. Keep boxes upright.
Storage	Store indoor, clean and dry, away from direct sunlight in a cool place below +45°C. Unlimited shelf life.