

STOPAQ® THERMOWRAP

Product Information

Product description: Stopaq® Thermowrap is a heat reflective composite tape made of an aluminium foil backing with a fibreglass fabric wire harness reinforcement and a high temperature silicone adhesive.

Stopaq® Thermowrap is used in applications where Stopaq® corrosion preventing coating materials have to be protected against exposure to excessive heat.

Features:

- High temperature resistance
- Good heat reflective properties
- Flame retardant
- Self-extinguishing

Benefits:

- Single coated construction
- Hand-tearable
- Conforms to irregular shapes
- Consistent unwinding

Application examples

Heat shielding: Protection of Stopaq® corrosion preventing coating systems from exposure to excessive heat.

General order information

Product	Stopaq® Thermowrap is available in rolls, wound on cardboard coils, packed in cardboard boxes.
Art. Nr.: 1262	Contents: 100mmx 30m, 27 rolls/box
Handling	Handle with care. Keep boxes upright.
Storage	Store indoor, clean and dry, preferably at a temperature of +15 to +25°C. Shelf life at +25°C: 12 months

Application instructions

Specific coating applications	See specific Stopaq coating instructions for e.g. pipe wrapping, etc.
--------------------------------------	---

Handling and commissioning

Exposure to loads	Coated objects should not be exposed to excessive loads e.g. from lifting equipment.
Commissioning	Bringing into service is possible immediately after completion of the coating application.

Information

Documentation	Extensive information is available on our website. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending email to info@sealforlife.com
Certified staff	Application of the described coating system should be carried out by certified personnel.

Product properties Stopaq® Thermowrap

Colour	Metallic shine
Thickness	0.16 mm
Temperature range	Continuous operation: Up to +175°C Excursion temp.: +250°C
Adhesion to backing	≥ 0.3 N/mm (ASTM D-1000)
Tensile strength	≥ 19 N/mm (ASTM D-1000)
Flame resistance	Self-extinguishing (ISO 3795)



PART OF THE BERRY PLASTICS ENGINEERED MATERIALS DIVISION
Anodeflex® – Stopaq® – Polyken® – Covalence® – Powercrete®

SEAL FOR LIFE INDUSTRIES

Part of Berry Plastics Corporation
Gasselterstraat 20, 9503 JB Stadskanaal, the Netherlands
P.O. Box 285, 9500 AG Stadskanaal, the Netherlands
T: +31 (0) 599 696 170 / F: +31 (0) 599 696 177
E: info@sealforlife.com / I: www.sealforlife.com